

SUNLIGHT 48V 775Ah Traction Battery

Battery / Accu | SUNLIGHT | 0261876-SL



PzS tubular plate technology provides superior cycle life and deep discharge capability, preventing premature battery failure during intensive multi-shift operations. This 48V 775Ah traction battery ensures extended operational continuity for your electric fleet.

Features

- Delivering 775Ah of sustained power, this battery ensures your electric fleet operates for extended shifts, minimizing costly interruptions and maximizing productivity.
- Engineered for electric forklifts and material handling equipment, this battery is built for the high-demand cycles of warehouse and logistics operations.
- Utilizing PzS tubular plate technology, this battery offers superior cycle life and deep discharge capability compared to standard flat plate designs, ensuring greater long-term value.
- Features integrated aqua+ and REMA 320 connectors for enhanced safety, ease of connection, and efficient maintenance of your motive power systems.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
48 V	775 Ah	1.138 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	48 V
Chemistry	Lead-Acid	Rated Capacity (C20)	775 Ah
Physical Specifications			
Length	220 mm		
Width	424 mm		
Height	784 mm		
Weight	1.138 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0261876-SL**
 Manufacturer Code: **5 PzS**