

SUNLIGHT 80V 465Ah Traction Battery

Battery / Accu | SUNLIGHT | 0261882-SL



PzS tubular plates ensure deep discharge resilience for intensive use. This 80V, 465Ah battery maximizes electric fleet uptime for demanding logistics and warehousing.

Features

- Sustained 80V output and 465Ah capacity ensure extended operational periods for your electric fleet, reducing the need for frequent charging and maximizing equipment uptime.
- Engineered for intensive material handling applications, including electric forklifts and AGVs, ensuring reliable power delivery in demanding logistics and warehousing environments.
- Utilizes advanced PzS tubular plate technology for superior cycle life and deep discharge capabilities, offering greater resilience and longevity in heavy-duty traction applications.
- Equipped with aqua+ and REMA 320 connectors for enhanced safety, ease of connection, and robust integration into existing industrial charging infrastructure.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
80 V	465 Ah	1,207 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	80 V
Chemistry	Lead-Acid	Rated Capacity (C20)	465 Ah
Physical Specifications			
Length	25 mm		
Width	564 mm		
Height	784 mm		
Weight	1,207 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0261882-SL**
 Manufacturer Code: **3 PzS**