

SUNLIGHT 80V 620Ah Traction Battery

Battery / Accu | SUNLIGHT | 0261883-SL



Multi-shift traction cycles demand a battery that sustains discharge depth without capacity loss; PzS tubular plate technology delivers superior cycle life and deep discharge resilience. This 80V 620Ah unit integrates a watering system for extended operational continuity in demanding industrial logistics.

Features

- Extended operational capacity of 620Ah ensures your electric vehicles remain productive throughout extended shifts, reducing the frequency of costly downtime.
- Specifically engineered for the rigorous demands of electric forklifts, pallet trucks, and other material handling equipment in industrial logistics and manufacturing.
- Features PzS tubular plate technology, delivering superior cycle life and deep discharge capabilities compared to standard flat-plate designs for consistent, long-term power delivery.
- Includes the aqua+REMA320 system for enhanced safety and efficient watering, ensuring optimal battery health and simplified maintenance procedures.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
80 V	620 Ah	1,532 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	80 V
Chemistry	Lead-Acid	Rated Capacity (C20)	620 Ah
Physical Specifications			
Length	25 mm		
Width	708 mm		
Height	784 mm		
Weight	1,532 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0261883-SL**
 Manufacturer Code: **4 PzS**