

EXIDE 24V 225Ah Traction Battery (Complete)

Battery / Accu | EXIDE | 0263453-EX



When specifying a traction battery for extended operational periods, the 225Ah capacity and 675(nok) rating directly determine work output per charge. This complete 24V system integrates an aqua+ system and REMA 160 connector for enhanced safety and efficient power management in demanding environments.

Features

- The 225Ah capacity ensures extended operational periods for industrial equipment, minimizing downtime and maximizing work output per charge.
- Engineered for heavy-duty material handling and logistics applications, including forklifts and AGVs, ensuring reliable performance in demanding environments.
- Features an integrated aqua+ system and REMA 160 connector for enhanced safety and efficient power management, alongside a 675(nok) rating for high discharge demands.
- Built for resilience and longevity in high-cycle industrial settings, providing dependable power delivery and a robust solution for continuous operations.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
24 V	225 Ah	199 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery (Complete)	Nominal Voltage	24 V
Chemistry	Lead-Acid	Rated Capacity (C20)	225 Ah
Physical Specifications			
Length	643 mm		
Width	195 mm		
Height	569 mm		
Weight	199 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0263453-EX**
 Manufacturer Code: **3 EPzB**