EXIDE 24V 225Ah Traction Battery (Complete)

Battery / Accu | EXIDE | 0263453-EX



When specifying a traction battery for extended operational periods, the 225Ah capacity and 675(nok) rating directly determine work output per charge. This complete 24V system integrates an aqua+ system and REMA 160 connector for enhanced safety and efficient power management in demanding environments.

Features

- The 225Ah capacity ensures extended operational periods for industrial equipment, minimizing downtime and maximizing work output per charge.
- Engineered for heavy-duty material handling and logistics applications, including forklifts and AGVs, ensuring reliable performance in demanding environments.
- Features an integrated aqua+ system and REMA 160 connector for enhanced safety and efficient power management, alongside a 675(nok) rating for high discharge demands.
- Built for resilience and longevity in high-cycle industrial settings, providing dependable power delivery and a robust solution for continuous operations.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
24 V	**225 Ah**	**199 kg**

Technical Specifications

General Information

Technology	**Traction Battery (Complete)**
Chemistry	**Lead-Acid**

Physical Specifications

Length	**643 mm**
Width	**195 mm**
Height	**569 mm**
Weight	**199 kg**

Electrical Specifications

Nominal Voltage	**24 V**
Rated Capacity (C20)	**225 Ah**

Regulatory Compliance

Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3

Regulatory: CE | Bebat | ADR

Product Identification

Item Code:	**0263453-EX**
Manufacturer Code:	**3 EPzB**

Specifications are subject to change without notice. © 2026 De Hoeve Multipower B.V.