

SUNLIGHT 24V 225Ah Traction Battery

Battery / Accu | SUNLIGHT | 0263453-SL



Tubular plate tech manages electrolyte levels, preventing deep discharge degradation and sustaining 225Ah capacity for extended shifts. Its robust construction integrates seamlessly with electric material handling equipment for maximum uptime and lower total cost of ownership.

Features

- Sustained 225Ah capacity ensures your electric vehicles operate for extended shifts, reducing charge cycles and maximizing operational uptime for material handling equipment.
- Engineered for the rigorous demands of industrial environments, making it ideal for forklifts, pallet trucks, and other electric vehicles in logistics and manufacturing.
- Tubular plate technology (PzB) delivers superior deep cycling capability and extended service life compared to standard flat plate designs, ensuring a lower total cost of ownership.
- Designed with robust construction and integrated aqua+REMA160 connectors for reliable power delivery and enhanced connectivity in demanding applications.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
24 V	225 Ah	199 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	24 V
Chemistry	Lead-Acid	Rated Capacity (C20)	225 Ah
Physical Specifications			
Length	643 mm		
Width	195 mm		
Height	569 mm		
Weight	199 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0263453-SL**