

SUNLIGHT 48V 620Ah Traction Battery

Battery / Accu | SUNLIGHT | 0263864-SL



Demanding multi-shift industrial operations require sustained energy output for continuous equipment productivity. PzS tubular plate technology provides superior cycle life and energy efficiency compared to standard flat plate designs, extending operational value in forklift fleets and industrial electric vehicles.

Features

- Delivers sustained energy output for full-shift operation, ensuring your material handling equipment remains productive throughout demanding work cycles.
- Engineered for intensive use in forklift fleets, electric pallet trucks, and other industrial electric vehicles within busy warehouse and manufacturing environments.
- Features PzS tubular plate technology, providing superior cycle life and energy efficiency compared to standard flat plate designs for long-term operational value.
- Includes the aqua+ system and REMA 320 connector for enhanced safety, simplified watering, and reliable electrical connections in demanding conditions.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
48 V	620 Ah	936 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	48 V
Chemistry	Lead-Acid	Rated Capacity (C20)	620 Ah
Physical Specifications			
Length	32 mm		
Width	440 mm		
Height	784 mm		
Weight	936 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0263864-SL**
 Manufacturer Code: **4 PzS**