

SUNLIGHT 48V 930Ah Traction Battery

Battery / Accu | SUNLIGHT | 0265237-SL



High 930Ah capacity sustains extended operational uptime, minimising fleet downtime and reducing charge frequency for maximum productivity. DIN-C compliance and integrated aqua+REMA320 connection ensure reliable performance and simplified maintenance in demanding industrial applications.

Features

- Experience extended operational uptime and reduced charging cycles thanks to the high 930Ah capacity, maximizing your fleet's productivity.
- Engineered for intensive use in electric forklifts and industrial vehicles within demanding warehouse and logistics environments.
- Benefit from DIN-C compliance and integrated aqua+REMA320 connection system for reliable performance and simplified maintenance.
- Designed for robust industrial applications, ensuring dependable power delivery in continuous duty cycles.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT
48 V	930 Ah	1.364 kg

Technical Specifications

General Information		Electrical Specifications	
Technology	Traction Battery	Nominal Voltage	48 V
Chemistry	Lead-Acid	Rated Capacity (C20)	930 Ah
Physical Specifications			
Length	220 mm		
Width	496 mm		
Height	784 mm		
Weight	1.364 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **0265237-SL**
 Manufacturer Code: **6 PzS**