

SPE 12V 30A Industrial Charger

Battery Charger / Acculader | SPE | CBHF2



Multi-voltage output capability delivers 30A to 12V/24V and 20A to 48V systems, supporting diverse industrial equipment. Its robust 3.5kg construction ensures high operational continuity in demanding applications.

Features

- Delivers rapid 30A charging current to minimize equipment downtime and maximize operational efficiency.
- Engineered for demanding applications including forklifts, marine, heavy-duty vehicles, and golf cars.
- Robust 3.5kg construction ensures durability and reliability in tough industrial environments.
- Designed for 12V systems, providing essential power for a wide range of industrial equipment.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
12 V	30 A	3,5 kg

Technical Specifications

Output		Connectivity & Protection	
Nominal Output Voltage	12 V	Reverse Polarity Protection	? Yes
Max Output Current	30 A	Short Circuit Protection	? Yes
Supported Voltages	12V/24V/36V/48V		
Physical Specifications			
Length	180 mm		
Width	310 mm		
Height	100 mm		
Weight	3,5 kg		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
 Regulatory: CE

Product Identification

Item Code: **CBHF2**
 Manufacturer Code: **CBHF2**
 Model: **CBHF2**