

SPE 24V 40A Industrial Charger

Battery Charger / Acculader | SPE | CBHF2XP12



Rapid 40A charging current ensures heavy-duty equipment is operational faster, minimizing costly downtime. Engineered for demanding Heftruck, Marine, and Golf Car environments, this charger provides optimized 24V output to prolong industrial battery service life and maintain peak performance.

Features

- Delivers rapid 40A charging current, ensuring your heavy-duty equipment is operational faster and minimizing costly downtime.
- Specifically engineered for demanding applications in Heftruck, Marine, and Golf Car environments, providing reliable power where it's needed most.
- Optimized 24V output ensures efficient and safe charging for industrial-grade batteries, prolonging their service life and maintaining peak performance.
- Robust construction designed for industrial settings, offering dependable operation and protection against the rigors of daily use.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
12 V	40 A	3,5 kg

Technical Specifications

Output		Connectivity & Protection	
Nominal Output Voltage	12 V	Reverse Polarity Protection	? Yes
Max Output Current	40 A	Short Circuit Protection	? Yes
Supported Voltages	12V/24V		
Physical Specifications			
Length	180 mm		
Width	310 mm		
Height	100 mm		
Weight	3,5 kg		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
 Regulatory: CE

Product Identification

Item Code: **CBHF2XP12**
 Manufacturer Code: **CBHF2XP12**
 Model: **CBHF2XP12**