

SPE 36V 30A Industrial Charger

Battery Charger / Acculader | SPE | CBHF2XP36



Across fixed and mobile DC power systems where re-installation is impractical, a rapid 30A charging current minimizes equipment downtime and sustains operational readiness. Its robust 3.5kg construction signifies durability, designed for long-term performance in industrial settings.

Features

- Rapid 30A charging current minimizes equipment downtime, ensuring your fleet or machinery is always ready for demanding tasks.
- Engineered for heavy-duty applications including forklifts, marine, and golf cars, providing reliable power in challenging operational environments.
- Robust construction with a 3.5kg weight signifies durability and stability, designed for long-term performance in industrial settings.
- Optimized 36V output voltage is specifically matched to the requirements of industrial battery systems for efficient and safe charging.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
36 V	30 A	3,5 kg

Technical Specifications

Output		Connectivity & Protection	
Nominal Output Voltage	36 V	Reverse Polarity Protection	? Yes
Max Output Current	30 A	Short Circuit Protection	? Yes
Supported Voltages	36V/48V		
Physical Specifications			
Weight	3,5 kg		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
 Regulatory: CE

Product Identification

Item Code: **CBHF2XP36**
 Manufacturer Code: **CBHF2XP36**
 Model: **CBHF2XP36**