

IEB 24V 40A Industrial Charger

Battery Charger / Acculader | IEB | E230G24-40.B50-FP

40A current delivery for 24V lead-acid batteries overcomes extended recharge times, ensuring rapid replenishment for demanding industrial applications. Its IP21 rating provides protection against vertically falling water droplets, enabling safe operation in protected indoor industrial environments.



Features

- Delivers a powerful 40A charging current, ensuring rapid and efficient replenishment of 24V lead-acid batteries to minimize equipment downtime.
- Engineered for industrial environments, providing reliable power management for logistics, manufacturing, and warehousing operations.
- Features an IP21 rating, offering protection against vertically falling water droplets for safe operation in protected indoor industrial spaces.
- Specifically designed for lead-acid (PB) battery chemistries, ensuring optimal charging performance and battery longevity.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
24 V	40 A	12 kg

Technical Specifications

Output		Charging Features	
Nominal Output Voltage	24 V	Supported Battery Types	Lead-acid
Max Output Current	40 A	Physical Specifications	
Connectivity & Protection		Weight	12 kg
Reverse Polarity Protection	? Yes	IP Rating	IP21
Short Circuit Protection	? Yes		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code: **E230G24-40.B50-FP**
Model: **E230G24-40.B50-FP**