

# EXIDE 12V 75Ah Starter Battery

Battery / Accu | EXIDE | EA754



Robust 630A cold-cranking power delivers reliable engine starts in any temperature, preventing operational downtime. Engineered for passenger vehicles and light commercial trucks, it provides essential ignition power for daily transport and logistics.

### Features

- Delivers robust 630A cold-cranking power for reliable engine starts in any temperature, ensuring your operations remain uninterrupted.
- Engineered for passenger vehicles and light commercial trucks, providing dependable ignition power essential for daily transport and logistics.
- Utilizes advanced lead-acid technology for consistent power delivery and extended service life, reducing replacement frequency and total cost of ownership.
- Designed with a standard terminal configuration and compact dimensions for straightforward integration into a wide range of vehicle battery trays.

| NOMINAL VOLTAGE | RATED CAPACITY (C20) | COLD CRANKING AMPS (EN) | WEIGHT         | HOLD-DOWN TYPE |
|-----------------|----------------------|-------------------------|----------------|----------------|
| <b>12 V</b>     | <b>75 Ah</b>         | <b>630 A</b>            | <b>17,4 kg</b> | <b>B01</b>     |

## Technical Specifications

| General Information            |                        | Electrical Specifications |              |
|--------------------------------|------------------------|---------------------------|--------------|
| Technology                     | <b>Starter Battery</b> | Nominal Voltage           | <b>12 V</b>  |
| Chemistry                      | <b>Lead-Acid</b>       | Rated Capacity (C20)      | <b>75 Ah</b> |
| <b>Physical Specifications</b> |                        | Cold Cranking Amps (EN)   | <b>630 A</b> |
| Length                         | <b>270 mm</b>          | <b>Layout</b>             |              |
| Width                          | <b>173 mm</b>          | Terminal Position         | <b>+R</b>    |
| Height                         | <b>222 mm</b>          | Hold-Down Type            | <b>B01</b>   |
| Weight                         | <b>17,4 kg</b>         |                           |              |

### Regulatory Compliance

**CE** Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3  
 Regulatory: CE | Bebat | ADR

### Product Identification

Item Code: **EA754**