

EXIDE GEL 12V 25Ah Starter Battery

Battery / Accu | EXIDE | ES290



When evaluating starter batteries for demanding automotive applications, 240A CCA ensures engine ignition in all weather conditions, keeping your fleet operational. Advanced gel technology provides superior deep discharge tolerance and maintenance-free operation, reducing downtime.

Features

- Reliable starting power with 240A CCA ensures engine ignition in all weather conditions, keeping your fleet operational.
- Designed for the automotive sector, this battery is engineered for cars, light commercial vehicles, and other engine-powered applications.
- Advanced gel technology provides superior deep discharge tolerance and maintenance-free operation, reducing downtime.
- Sealed construction offers exceptional vibration resistance, safeguarding against premature failure in demanding environments.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	25 Ah	240 A	9,6 kg	B00

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	25 Ah
Physical Specifications		Cold Cranking Amps (EN)	240 A
Length	166 mm	Layout	
Width	175 mm	Terminal Type	STUD_M5
Height	125 mm	Terminal Position	+R
Weight	9,6 kg	Hold-Down Type	B00
Case Type	P24		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **ES290**
 EAN/Barcode: **3661024035866**
 Manufacturer Code: **ES290**