

VARTA Dynamic SLI 12V 80Ah Starter Battery

Battery / Accu | VARTA | F17



Immediate, reliable engine starts are ensured by 740A of cold-cranking power, even in sub-zero temperatures. This proven lead-acid technology integrates directly into passenger cars and light commercial vehicles for dependable ignition.

Features

- Delivers 740A of cold-cranking power, ensuring immediate and reliable engine starts even in sub-zero temperatures.
- Engineered for demanding automotive applications, from everyday passenger cars to light commercial vehicles.
- Utilizes proven lead-acid technology, optimized for the high-current demands of engine starting.
- Features a robust design built to withstand the vibrations and stresses of regular vehicle operation.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	80 Ah	740 A	19,21 kg	B13

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	80 Ah
Physical Specifications		Cold Cranking Amps (EN)	740 A
Length	315 mm	Layout	
Width	175 mm	Terminal Type	AUTOMOTIVE
Height	175 mm	Terminal Position	+R
Weight	19,21 kg	Hold-Down Type	B13
Case Type	T7/LB4		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **F17**
 EAN/Barcode: **4016987167687**
 Manufacturer Code: **F17**
 Model: **Dynamic SLI**