

VARTA Dynamic SLI 12V 90Ah Starter Battery

Battery / Accu | VARTA | F6



Without 720A cold-cranking power, engine starts in adverse weather risk failure and costly downtime. This VARTA battery delivers dependable ignition performance, utilising proven lead-acid technology for automotive applications.

Features

- Delivers 720A cold-cranking power, ensuring reliable engine starts in any weather condition and preventing costly downtime.
- Specifically engineered for automotive applications, providing the essential power for passenger cars and light commercial vehicles.
- Utilizes proven lead-acid technology for a dependable and cost-effective starting power solution.
- Designed with standard DIN B13 (L5) terminal configuration for straightforward installation and compatibility with most European vehicle models.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	90 Ah	720 A	20,78 kg	B13

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	90 Ah
Physical Specifications		Cold Cranking Amps (EN)	720 A
Length	353 mm	Layout	
Width	175 mm	Terminal Type	AUTOMOTIVE
Height	190 mm	Terminal Position	+R
Weight	20,78 kg	Hold-Down Type	B13
Case Type	H8/L5		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **F6**
 EAN/Barcode: **4016987167809**
 Manufacturer Code: **F6**
 Model: **Dynamic SLI**