VARTA Dynamic SLI 12V 90Ah Starter Battery

Battery / Accu | VARTA | F6



Without 720A cold-cranking power, engine starts in adverse weather risk failure and costly downtime. This VARTA battery delivers dependable ignition performance, utilising proven lead-acid technology for automotive applications.

Features

- Delivers 720A cold-cranking power, ensuring reliable engine starts in any weather condition and preventing costly downtime.
- Specifically engineered for automotive applications, providing the essential power for passenger cars and light commercial vehicles.
- Utilizes proven lead-acid technology for a dependable and cost-effective starting power solution.
- Designed with standard DIN B13 (L5) terminal configuration for straightforward installation and compatibility with most European vehicle models.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	**90 Ah**	**720 A**	**20,78 kg**	**B13**

Technical Specifications

General Information

Technology	**Starter Battery**
Chemistry	**Lead-Acid**

Physical Specifications

Length	**353 mm**
Width	**175 mm**
Height	**190 mm**
Weight	**20,78 kg**
Case Type	**H8/L5**

Electrical Specifications

Nominal Voltage	**12 V**
Rated Capacity (C20)	**90 Ah**
Cold Cranking Amps (EN)	**720 A**

Layout

Terminal Type	**AUTOMOTIVE**
Terminal Position	**+R**
Hold-Down Type	**B13**

Regulatory Compliance

CE

Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3

Regulatory: CE | Bebat | ADR

Product Identification

Item Code:	**F6**
EAN/Barcode:	**4016987167809**
Manufacturer Code:	**F6**
Model:	**Dynamic SLI**

Specifications are subject to change without notice. © 2026 De Hoeve Multipower B.V.