

FULLRIVER FT500 AGM 12V 40Ah Starter Battery

Battery / Accu | FULLRIVER | FT500



500A cold cranking power ensures reliable engine starts even in sub-zero temperatures, maintaining operational continuity. Engineered specifically for marine motor applications, its AGM technology provides spill-proof, maintenance-free operation and superior vibration resistance.

Features

- 500A cold cranking power ensures reliable engine starts even in sub-zero temperatures, minimizing downtime and ensuring immediate operational readiness.
- Engineered specifically for marine motor applications, providing dependable starting power and vibration resistance crucial for onboard vessels.
- AGM technology offers a completely sealed and maintenance-free design, eliminating the need for watering and providing enhanced safety through spill-proof operation.
- Featuring secure M6 terminals for robust and reliable electrical connections, ensuring optimal power transfer and long-term durability.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	40 Ah	500 A	15 kg	B00

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	40 Ah
Physical Specifications		Cold Cranking Amps (EN)	500 A
Length	250 mm	Reserve Capacity	70 min
Width	97 mm	Layout	
Height	206 mm	Terminal Type	STUD_M6
Weight	15 kg	Terminal Position	+R
Case Type	N.B.	Hold-Down Type	B00
Operating Conditions			
Max Operating Temp	71 °C		

Regulatory Compliance



Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
Regulatory: CE | Bebat | ADR

Product Identification

Item Code: FT500
Manufacturer Code: FT500
Model: FT500