

SONNENSCHIN 196Ah Stationary Battery

Battery / Accu | SONNENSCHIN | GF12.160V

Critical systems need deep-cycle reserve power for continuous high-load operation. Advanced GEL technology offers 196Ah sustained capacity with superior deep discharge tolerance for extended continuity in telecom, security, and renewables.



Features

- Sustain critical operations with 196Ah of deep-cycle reserve power, ensuring uninterrupted service for essential equipment.
- Engineered for continuous use in telecommunications, security, and renewable energy storage applications.
- Advanced GEL technology provides superior deep discharge tolerance and maintenance-free operation for enhanced reliability.
- Designed for robust integration into stationary power systems, offering dependable performance and extended lifespan.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT	HOLD-DOWN TYPE
12 V	196 Ah	62,5 kg	B00

Technical Specifications

General Information		Electrical Specifications	
Technology	Stationary Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	196 Ah
Physical Specifications		Layout	
Length	518 mm	Terminal Position	+L
Width	274 mm	Hold-Down Type	B00
Height	238 mm		
Weight	62,5 kg		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **GF12.160V**