

GYS BATIUM 15.24 Fast Charger

Battery Charger / Acculader | GYS | GYS024526



Without optimal battery condition, premature replacement and operational downtime are inevitable. The GYS BATIUM 15.24 employs multi-stage charging algorithms to sustain peak battery health for automotive workshops and fleet maintenance.

Features

- Ensures optimal battery condition to maximize operational uptime and reduce premature replacement needs
- Designed for automotive workshops, fleet maintenance, and agricultural equipment applications
- Provides consistent and reliable power for essential battery maintenance tasks
- Built for demanding professional environments, ensuring durability and long-term performance

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	INPUT VOLTAGE MAX	WEIGHT
24 V	15 A	230 V	6,2 kg

Technical Specifications

Input		Output	
Input Voltage Min	230 V	Nominal Output Voltage	24 V
Input Voltage Max	230 V	Max Output Current	15 A
Input Frequency	50/60 Hz	Supported Voltages	6 / 12 / 24 V
Input Power	450 W	Connectivity & Protection	
Charging Features		Reverse Polarity Protection	? Yes
Charge Stages	3	Short Circuit Protection	? Yes
Supported Battery Types	gel, vloeibaar, AGM, Vrla		
Physical Specifications			
Length	362 mm		
Width	212 mm		
Height	140 mm		
Weight	6,2 kg		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code: GYS024526
EAN/Barcode: 3154020024526
Manufacturer Code: 024526
Model: BATIUM 15.24