

LEOCH AGM 12V 100Ah Deep Cycle Battery

Battery / Accu | LEOCH | LDC12-100



Extended operational periods for critical equipment are ensured by a 100Ah capacity, directly minimizing downtime in stationary power architectures. This stationary battery leverages LEOCH's proven technology for consistent and dependable energy discharge in telecommunications, UPS, and emergency lighting.

Features

- Ensures extended operational periods for critical equipment with a substantial 100Ah capacity, minimizing downtime.
- Engineered for stable power in stationary applications such as telecommunications, UPS systems, and emergency lighting.
- Leverages LEOCH's proven battery technology for consistent and dependable energy discharge.
- Compact dimensions (260x168x214mm) and a weight of 25.8kg facilitate straightforward installation in confined spaces.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	WEIGHT	TERMINAL TYPE
12 V	100 Ah	25,8 kg	T6(M6)

Technical Specifications

General Information		Electrical Specifications	
Technology	Deep Cycle Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	100 Ah
Physical Specifications		Reserve Capacity	192 min
Length	260 mm	Layout	
Width	168 mm	Terminal Type	T6(M6)
Height	214 mm		
Weight	25,8 kg		
Operating Conditions			
Max Operating Temp	55 °C		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **LDC12-100**
 Model: **LDC**