

LESTER Summit 48V 22A Industrial Charger

Battery Charger / Acculader | LESTER | Lester30410

Ingress protection to IP66 ensures operation in harsh industrial settings, delivering 22A to rapidly restore power and minimise downtime for critical equipment. Its versatile 24-48V input voltage range offers broad compatibility across diverse power sources and installation locations.



Features

- Delivers a substantial 22A charging current to rapidly restore power, minimizing operational downtime for your essential equipment.
- Engineered for harsh industrial and outdoor environments, with an IP66 rating providing complete dust protection and resistance to powerful water jets.
- Features a versatile 24-48V input voltage range, offering adaptability across various power sources and locations.
- Compact and lightweight at only 1.1kg, the Summit charger integrates seamlessly into existing systems without compromising space or adding undue weight.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
24 V	22 A	1,1 kg

Technical Specifications

Output		Connectivity & Protection	
Nominal Output Voltage	24 V	Reverse Polarity Protection	? Yes
Max Output Current	22 A	Short Circuit Protection	? Yes
Physical Specifications			
Weight	1,1 kg		
IP Rating	IP66		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code: **Lester30410**
Manufacturer Code: **Lester30410**
Model: **Summit**