

CTEK 12V 3.6A Smart Charger

Battery Charger / Acculader | CTEK | MXS.3.8



Without robust IP65 ingress protection, seasonal vehicles risk battery damage from dust and water ingress. This CTEK smart charger delivers a consistent 3.6A current and actively maintains battery health to prevent overcharging and extend lifespan.

Features

- Ensures dependable battery readiness with a consistent 3.6A charging current, ideal for maintaining seasonal vehicles.
- Engineered for outdoor and marine use, the IP65 rating provides full protection against dust and powerful water jets.
- Intelligent charging technology actively maintains battery health, preventing overcharging and extending battery lifespan.
- Robust construction with an IP65 rating guarantees reliable operation in harsh automotive, caravan, camper, and marine environments.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	INPUT VOLTAGE MAX	WEIGHT
12 V	3,6 A	240 V	0,85 kg

Technical Specifications

Input		Output	
Input Voltage Min	220 V	Nominal Output Voltage	12 V
Input Voltage Max	240 V	Max Output Current	3,6 A
Input Frequency	50-60 Hz	Supported Voltages	12V
Charging Features		Connectivity & Protection	
Charge Stages	7	Reverse Polarity Protection	? Yes
Supported Battery Types	WET, MF, Ca/Ca, AGM, GEL	Short Circuit Protection	? Yes
Physical Specifications			
Length	168 mm		
Width	65 mm		
Height	38 mm		
Weight	0,85 kg		
IP Rating	IP65		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code: **MXS.3.8**
Manufacturer Code: **MXS.3.8**
Model: **MXS.3.8**