

TBS-ELECTRONICS 24V 30A Multi-Bank Charger

Battery Charger / Acculader | TBS-ELECTRONICS | OC2-24-30



Engineered for demanding environments, this 24V 30A multi-bank charger offers rapid 30A charging to minimize vehicle or equipment downtime. Its versatile application across automotive, camper, marine, and heavy-duty sectors ensures robust and consistent battery charging performance.

Features

- Rapid 30A charging current minimizes vehicle or equipment downtime, ensuring faster readiness for operation.
- Engineered for diverse applications including Automotive, Camper, Marine, and Heavy Duty sectors, providing versatile power solutions.
- Delivers a stable 24V output, optimized for larger systems requiring robust and consistent battery charging performance.
- Built for reliable operation in demanding environments, ensuring consistent power delivery across various operational conditions.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	WEIGHT
24 V	30 A	4 kg

Technical Specifications

Output		Connectivity & Protection	
Nominal Output Voltage	24 V	Reverse Polarity Protection	? Yes
Max Output Current	30 A	Short Circuit Protection	? Yes
Physical Specifications			
Length	351 mm		
Width	210 mm		
Height	114 mm		
Weight	4 kg		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code: **OC2-24-30**
Manufacturer Code: **OC2-24-30**
Model: **OC2-24-30**