

OPTIMA Red Top AGM 12V 50Ah Starter Battery

Battery / Accu | OPTIMA | RTR-4.2



Delivers 815 CCA for reliable engine starting even in sub-zero temperatures, eliminating operational delays. Specifically engineered for agricultural machinery, its advanced AGM technology offers exceptional vibration resistance and a sealed, maintenance-free design.

Features

- Delivers 815 CCA for reliable engine starting even in sub-zero temperatures, minimizing operational delays and ensuring productivity.
- Specifically engineered for the rigorous demands of agricultural machinery, offering exceptional vibration resistance and durability in tough field conditions.
- Features advanced AGM technology for a completely sealed, maintenance-free design, eliminating the need for watering and reducing risk of leaks or corrosion.
- Designed for high-demand starting applications, providing the consistent power reserves necessary for repeated engine starts in challenging agricultural environments.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
12 V	50 Ah	815 A	17,2 kg	B00

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	12 V
Chemistry	Lead-Acid	Rated Capacity (C20)	50 Ah
Physical Specifications		Cold Cranking Amps (EN)	815 A
Length	254 mm	Layout	
Width	175 mm	Terminal Type	AUTOMOTIVE
Height	200 mm	Terminal Position	+R
Weight	17,2 kg	Hold-Down Type	B00
Case Type	34R		

Regulatory Compliance

CE Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
 Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **RTR-4.2**
 EAN/Barcode: **8719325860405**
 Manufacturer Code: **RTR-4.2**
 Model: **Red Top**