

OPTIMA Red Top AGM 6V 50Ah Starter Battery

Battery / Accu | OPTIMA | RTS-2.1.6V



815 CCA cold-cranking power ensures assured starting performance across demanding agricultural and caravan applications. Advanced AGM technology provides a maintenance-free, vibration-resistant, and spill-proof design for enhanced longevity and safety.

Features

- Delivers 815 CCA cold-cranking power for assured starting performance in any condition, keeping your agricultural machinery or caravan operational.
- Optimized for demanding Agri and Caravan applications, providing the robust starting power and reliability essential for continuous operation.
- Features advanced AGM (Absorbent Glass Mat) technology for a maintenance-free, vibration-resistant, and spill-proof design, enhancing longevity and safety.
- Designed with a sealed construction to withstand extreme temperatures and vibrations, ensuring dependable power delivery in rugged environments.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
6 V	50 Ah	815 A	8,3 kg	B00

Technical Specifications

General Information		Electrical Specifications	
Technology	Starter Battery	Nominal Voltage	6 V
Chemistry	Lead-Acid	Rated Capacity (C20)	50 Ah
Physical Specifications		Cold Cranking Amps (EN)	815 A
Length	255 mm	Reserve Capacity	100 min
Width	90 mm	Layout	
Height	206 mm	Terminal Type	AUTOMOTIVE
Weight	8,3 kg	Terminal Position	+L
Operating Conditions		Hold-Down Type	B00
Max Operating Temp	52 °C		

Regulatory Compliance



Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3
Regulatory: CE | Bebat | ADR

Product Identification

Item Code: **RTS-2.1.6V**
EAN/Barcode: **8719325860412**
Manufacturer Code: **RTS-2.1.(6V)**
Model: **Red Top**