OPTIMA Red Top AGM 6V 50Ah Starter Battery

Battery / Accu | OPTIMA | RTS-2.1.6V



815 CCA cold-cranking power ensures assured starting performance across demanding agricultural and caravan applications. Advanced AGM technology provides a maintenance-free, vibration-resistant, and spill-proof design for enhanced longevity and safety.

Features

- Delivers 815 CCA cold-cranking power for assured starting performance in any condition, keeping your agricultural machinery or caravan operational.
- Optimized for demanding Agri and Caravan applications, providing the robust starting power and reliability essential for continuous operation.
- Features advanced AGM (Absorbent Glass Mat) technology for a maintenance-free, vibration-resistant, and spill-proof design, enhancing longevity and safety.
- Designed with a sealed construction to withstand extreme temperatures and vibrations, ensuring dependable power delivery in rugged environments.

NOMINAL VOLTAGE	RATED CAPACITY (C20)	COLD CRANKING AMPS (EN)	WEIGHT	HOLD-DOWN TYPE
6 V	**50 Ah**	**815 A**	**8,3 kg**	**B00**

Technical Specifications

General Information

Technology	**Starter Battery**
Chemistry	**Lead-Acid**

Physical Specifications

Length	**255 mm**
Width	**90 mm**
Height	**206 mm**
Weight	**8,3 kg**

Operating Conditions

Max Operating Temp	**52 °C**

Electrical Specifications

Nominal Voltage	**6 V**
Rated Capacity (C20)	**50 Ah**
Cold Cranking Amps (EN)	**815 A**
Reserve Capacity	**100 min**

Layout

Terminal Type	**AUTOMOTIVE**
Terminal Position	**+L**
Hold-Down Type	**B00**

Regulatory Compliance

CE

Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3

Regulatory: CE | Bebat | ADR

Product Identification

Item Code:	**RTS-2.1.6V**
EAN/Barcode:	**8719325860412**
Manufacturer Code:	**RTS-2.1.(6V)**
Model:	**Red Top**

Specifications are subject to change without notice. © 2026 De Hoeve Multipower B.V.