

# OPTIMA Red Top AGM 12V 44Ah Starter Battery

Battery / Accu | OPTIMA | RTU-3.7



With 730 CCA, the OPTIMA Red Top ensures immediate ignition in challenging cold weather, preventing downtime. Its advanced AGM technology offers superior vibration resistance and maintenance-free operation for demanding agricultural and RV use.

### Features

- Delivers 730 CCA for confident engine starts in the most challenging cold weather conditions.
- Engineered for the rigorous demands of agricultural and recreational vehicle applications.
- Features advanced AGM technology for superior vibration resistance and maintenance-free operation.
- Built with robust casing and reliable terminal connections for dependable integration.

| NOMINAL VOLTAGE | RATED CAPACITY (C20) | COLD CRANKING AMPS (EN) | WEIGHT       | HOLD-DOWN TYPE |
|-----------------|----------------------|-------------------------|--------------|----------------|
| <b>12 V</b>     | <b>44 Ah</b>         | <b>730 A</b>            | <b>15 kg</b> | <b>B00</b>     |

## Technical Specifications

| General Information            |                        | Electrical Specifications |                  |
|--------------------------------|------------------------|---------------------------|------------------|
| Technology                     | <b>Starter Battery</b> | Nominal Voltage           | <b>12 V</b>      |
| Chemistry                      | <b>Lead-Acid</b>       | Rated Capacity (C20)      | <b>44 Ah</b>     |
| <b>Physical Specifications</b> |                        | Cold Cranking Amps (EN)   | <b>730 A</b>     |
| Length                         | <b>237 mm</b>          | <b>Layout</b>             |                  |
| Width                          | <b>172 mm</b>          | Terminal Type             | <b>AUT+FRONT</b> |
| Height                         | <b>197 mm</b>          | Terminal Position         | <b>+L</b>        |
| Weight                         | <b>15 kg</b>           | Hold-Down Type            | <b>B00</b>       |
| Case Type                      | <b>35</b>              |                           |                  |

### Regulatory Compliance



Standards: EN 50342, EN 61427, EN 62133, IEC 62619, UN 38.3  
 Regulatory: CE | Bebat | ADR

### Product Identification

Item Code: **RTU-3.7**  
 EAN/Barcode: **8719325860443**  
 Manufacturer Code: **RTU-3.7**  
 Model: **Red Top**