

CTEK 12V 0.8A Smart Charger

Battery Charger / Acculader | CTEK | XS.0.8



In dusty and wet operational environments, the IP65-rated construction prevents ingress of harmful contaminants, ensuring sustained battery charging performance. This controlled 0.8A smart charging process maintains battery health for automotive, caravan, camper, and marine applications during inactivity.

Features

- Maintains battery health with a controlled 0.8A charge, preventing degradation during periods of inactivity.
- Engineered for diverse applications including automotive, caravan, camper, and marine environments.
- IP65-rated protection ensures full resistance to dust and water jets, suitable for outdoor and wet conditions.
- Smart charging technology automatically optimizes the charging cycle for battery longevity and performance.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	INPUT VOLTAGE MAX	WEIGHT
12 V	0,8 A	240 V	0,3 kg

Technical Specifications

Input		Output	
Input Voltage Min	220 V	Nominal Output Voltage	12 V
Input Voltage Max	240 V	Max Output Current	0,8 A
Input Frequency	50-60 Hz	Supported Voltages	12V
Charging Features		Connectivity & Protection	
Charge Stages	6	Reverse Polarity Protection	? Yes
Supported Battery Types	WET, MF, Ca/Ca, AGM, GEL	Short Circuit Protection	? Yes
Physical Specifications			
Length	145 mm		
Width	55 mm		
Height	38 mm		
Weight	0,3 kg		
IP Rating	IP65		

Regulatory Compliance

CE Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
 Regulatory: CE

Product Identification

Item Code: **XS.0.8**
 Manufacturer Code: **XS.0.8**
 Model: **XS.0.8**