CTEK 12V 0.8A Smart Charger

Battery Charger / Acculader | CTEK | XS.0.8



In dusty and wet operational environments, the IP65-rated construction prevents ingress of harmful contaminants, ensuring sustained battery charging performance. This controlled 0.8A smart charging process maintains battery health for automotive, caravan, camper, and marine applications during inactivity.

Features

- Maintains battery health with a controlled 0.8A charge, preventing degradation during periods of inactivity.
- Engineered for diverse applications including automotive, caravan, camper, and marine environments.
- IP65-rated protection ensures full resistance to dust and water jets, suitable for outdoor and wet conditions.
- Smart charging technology automatically optimizes the charging cycle for battery longevity and performance.

NOMINAL OUTPUT VOLTAGE	MAX OUTPUT CURRENT	INPUT VOLTAGE MAX	WEIGHT
12 V	**0,8 A**	**240 V**	**0,3 kg**

Technical Specifications

Input

Input Voltage Min	**220 V**
Input Voltage Max	**240 V**
Input Frequency	**50-60 Hz**

Charging Features

Charge Stages	**6**
Supported Battery Types	**WET, MF, Ca/Ca, AGM, GEL**

Physical Specifications

Length	**145 mm**
Width	**55 mm**
Height	**38 mm**
Weight	**0,3 kg**
IP Rating	**IP65**

Output

Nominal Output Voltage	**12 V**
Max Output Current	**0,8 A**
Supported Voltages	**12V**

Connectivity & Protection

Reverse Polarity Protection	**? Yes**
Short Circuit Protection	**? Yes**

Regulatory Compliance

Standards: EN 60335-2-29, EN 55014, EN 61000-3-2
Regulatory: CE

Product Identification

Item Code:	**XS.0.8**
Manufacturer Code:	**XS.0.8**
Model:	**XS.0.8**

Specifications are subject to change without notice. © 2026 De Hoeve Multipower B.V.